

Document made available under the Patent Cooperation Treaty (PCT)

International application number: PCT/GB05/000555

International filing date: 16 February 2005 (16.02.2005)

Document type: Certified copy of priority document

Document details: Country/Office: GB
Number: 0403413.8
Filing date: 17 February 2004 (17.02.2004)

Date of receipt at the International Bureau: 09 May 2005 (09.05.2005)

Remark: Priority document submitted or transmitted to the International Bureau in compliance with Rule 17.1(a) or (b)



World Intellectual Property Organization (WIPO) - Geneva, Switzerland
Organisation Mondiale de la Propriété Intellectuelle (OMPI) - Genève, Suisse



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed




Dated

12 April 2005



The Patent Office

1/77



17FEB04 E873757-3 D00354
P01/7700 0.00-0403413.8 CHEQUE

Request for grant of a patent

(see the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference PBA/P089559PGB

2. Patent application numberA 17 FEB 2004 0403413.8
(The Patent Office will fill in this part)

3. Full name, address and postcode of the or of each applicant (*underline all surnames*) Nationwide Filter Company (Specialist Products) Limited
NFC House
Vickers Industrial Estate
Mellishaw Lane
Morecambe
Lancashire
LA3 3DY

Patents ADP number (*if you know it*)

06891329001
If the applicant is a corporate body, give the country/state of its incorporation UNITED KINGDOM

4. Title of the invention FILTER UNIT

5. Name of your agent (*if you have one*) Marks & Clerk

"Address for service" in the United Kingdom to which all correspondence should be sent (*including the postcode*) Sussex House
83-85 Mosley Street
Manchester
M2 3LG

Patents ADP number (*if you know it*) 18004 ✓

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (*if you know it*) the or each application number

| | Country | Priority application number (<i>if you know it</i>) | Date of filing (<i>day/month/year</i>) |
|--|---------|--|---|
| | | | |

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

| | Number of earlier application | Date of filing (<i>day/month/year</i>) |
|--|-------------------------------|---|
| | | |

8. Is a statement of Inventorship and of right to grant of a patent required in support of this request? (*Answer 'Yes' if:*
a) any applicant named in part 3 is not an inventor, or
b) there is an inventor who is not named as an applicant, or
c) any named applicant is a corporate body.
See note (d)) YES

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document

| | |
|----------------------------------|-----------------|
| Continuation sheets of this form | 0 |
| Description | 6 / |
| Claim(s) | 2 / |
| Abstract | |
| Drawing(s) | 2 + 2 <i>RL</i> |

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translations of priority documents

Statement of Inventorship and right to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and search (*Patents Form 9/77*)

Request for substantive examination (*Patents Form 10/77*)

Any other documents
(Please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

[Signature]
MARKS & CLERK

Date 16th February 2004

12. Name and daytime telephone number of person to contact in the United Kingdom

MR P. B. ATKINSON – 0161 233 5824

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.*
- Write your answers in capital letters using black ink or you may type them.*
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.*
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.*
- Once you have filled in the form you must remember to sign and date it.*
- For details of the fee and ways to pay please contact the Patent Office.*

FILTER UNIT

The present invention relates to filter units.

There are numerous types of filter unit of the type comprising a filter element located in a peripheral encasement frame with there being a seal between the periphery of the filter element and the frame. This seal ensures that all of the fluid to be filtered passes through the filter element itself and does not bypass this element by being able to pass between the periphery thereof and the encasement frame. Examples of filter elements used in such constructions are comprised of fibres, carbon packs, foams, electrostatic felts, meshes, scrims and other flat sheet media.

A particular example of such a filter unit is one incorporating a pleated filter element, such as a H.E.P.A. (High Efficiency Particulate Arrestor) filter element. Further examples of filter element include U.L.P.A. (Ultra Low Penetration Air) filters, ASHRAE media.

H.E.P.A. filter units are used in vacuum cleaners, respirators and many other air filtration applications. A H.E.P.A. filter element is pleated and is normally constructed from glass fibre or synthetic filtration sheet media. More particularly, the pleated element is formed by feeding the sheet media from a roll and applying transversely spaced lines of adhesive to the running web, one adjacent each longitudinal edge of the sheet media and usually several lines therebetween (the exact number depending on the width of the sheet media). Subsequently the sheet media is pleated (e.g. using a so-called 'minipleat' machine). In the resulting pleated element, the lines of adhesive serve to bond adjacent leaves of the pleats together.

Subsequently, the pleated element may be cut to shape and then sealed into a close fitting, preformed encasement frame (e.g. of metal or plastics material). Sealing of the pleated element into the frame is perhaps the most important step in the overall process for producing the H.E.P.A. filter unit since, a good seal ensures that all of the

air flow passes through the filtration media (with no bypass) so that the efficiency of the filter unit is dictated by the quality of the media and is unaffected by the seal.

However with current technology it is only really practical to produce H.E.P.A. filter units which are either rectangular (which term is also used to mean square) or circular.

In the case of rectangular units, two of the aforementioned glue lines (that bond the pleats together) will be located adjacent (and extend parallel to) two of the side edges of the frame. A sealing composition is then applied around the periphery of the front and rear faces of the pleated element. This composition seals onto the filter element and also onto the encasement frame. The sealing composition must extend sufficiently onto the margin of the filter element to ensure that a good seal is achieved. In particular, the composition extends as far as the outer glue lines (which are parallel to edges of the frame). Thus, in this case, the encasement procedure relies on the glue lines in the pleated pack to effect sealing.

The method used for sealing circular pleated filter elements into encasement frames is somewhat different and is called 'spinning' and does not rely on the glue lines in the pleated pack for the sealing process. More particularly the pleated element (formed as described above) is cut into a circle and placed into a close fitting peripheral encasement frame. The combination of the circular pleated element and the circular frame is then spun at high speed and the sealing composition is applied to the inside of the encasement frame whilst it is spinning. The centripetal force pushes the sealing composition outside onto the case wall where it builds up and seals the circular pleated element into position by 'coating' the open peripheral edges of the pleated pack.

The above described methods for producing rectangular or circular H.E.P.A. filter units are perfectly satisfactory. However difficulty is encountered if it is desired to produce a H.E.P.A. filter unit of other configurations. More particular, if the

filtering area of the unit is to be 'maximised' then it is necessary to have a relatively complicated pattern for the sealing composition around the periphery of the unit.

It is therefore an object of the present invention to obviate or mitigate the above mentioned disadvantages.

According to a first aspect of the present invention there is provided a method of forming a filter unit comprised of a filter element and an encircling peripheral encasement frame to which the filter element is sealed wherein the frame is moulded *in situ* by solidification of a liquid, solidifiable moulding composition provided around the periphery of the filter element.

According to a second aspect of the present invention there is provided a filter unit comprised of a filter element and a peripheral encasement frame sealed to the element wherein the frame has been moulded *in situ* around the filter element.

By moulding the peripheral encasement frame *in situ* around the periphery of the filter element from a solidifiable, liquid moulding composition there is produced a frame that is sealed to the filter element. Additionally, it is possible easily to mould encasement frames for filter elements which are other than rectangular or circular.

Preferably the moulding operation produces a frame that partially overlies a marginal region of at least one of the faces of the filter element.

The method of the invention may be effected by the steps of:

- (i) providing a filter element having front and rear faces and a bounding peripheral edge,
- (ii) locating around the peripheral edge of the element a mould unit which seals against peripheral regions of the front and rear faces and which together with the peripheral edge defines a mould cavity,
- (iii) filling the mould cavity with a solidifiable, liquid moulding composition,

- (iv) effecting conversion of the liquid to a solid, and
- (v) removing the mould thereby producing the filter element.

The solidifiable, liquid moulding composition may for example be a curable resin system or a molten thermoplastic resin that solidifies on cooling.

The filter element may, but not necessarily, be a pleated filter element. The invention is applicable particularly to the production of H.E.P.A. filter units but can also be applied to filter units comprising U.L.P.A. (Ultra Low Penetration Air) media, ASHRAE media and synthetic media including ePTFE laminate. The invention can equally well be used for the production of filter units in which the filter element comprises fibres, carbon packs, foams, electrostatic felts, meshes, scrims and other flat sheet media.

The invention has a number of advantages. These include, but are not limited to, the following:

- The filter unit can be created in any shape, curved or otherwise on more than one plane.
- A pleated filter unit can be created in any shape, curved or otherwise on more than one plane.
- The need for manufacture of a separate case for the filter unit is avoided.
- The invention enables two or more items to be encapsulated at the same time, e.g. a layer of pleated media and a foam pad.

Layers additional to the filter element may also be assembled with the latter to form a composite unit for encasement by the moulded, peripheral frame.

The invention will be further described by way of example only with reference to the accompanying drawings, in which:

Fig. 1 illustrates an example of a H.E.P.A. filter element of 'irregular' shape;

Fig. 2 schematically illustrates an arrangement for carrying out the method of the invention; and

Fig. 3. schematically illustrates formation of the peripheral encasement frame using the arrangement of Fig. 2.

Fig. 1 illustrates a H.E.P.A. filter element 1 formed of a pleated material (e.g. glass fibre or synthetic filtration sheet media) in which the leaves of the adjacent pleats are bonded together by lines of adhesive 2 that extend transversely to the pleats. As illustrated in Fig. 1, the element 1 has three straight edges and a fourth curved edge. Also marked on Fig. 1 by the dashed line 3 is the peripheral region of the element 1 to which sealing composition would need to be applied if the element 1 were to be mounted in a conventional preformed encasement frame (corresponding to the shape of the element 1). It will be seen that, at the curved edge, a step wise application of the sealing composition would be required to ensure adequate sealing whilst maintaining a maximum area of the element 1 free for filtration. The application of such a configuration of sealing composition would be exceedingly difficult using current technology.

Reference is now made to Fig. 2 which illustrates how a peripheral encasement frame may be formed (using the techniques of the invention) by moulding the frame *in situ* around the peripheral edges of a pleated H.E.P.A. filter element. More particularly, Fig.2 shows a H.E.P.A. filter element 10 which is considered to have upper and lower (as viewed in Fig. 2) major faces 11 and 12 as well as a peripheral edge 13. A mould 14 is located around the periphery of the filter element 10 and is configured to locate with clearance around the peripheral edge 13 and also around marginal regions 11a and 12a of the upper and lower faces 11 and 12 of the filter element 1. The mould does however have tapering projections 15 that bite slightly into the upper and lower faces 11 and 12 of the filter element so as to cause a slight depression therein (see insert to Fig. 2).

It will be appreciated from the foregoing description that the mould 14 and filter element 10 together form a mould cavity 15 that encircles the pleated element 10. This cavity 15 is defined, on the one hand, by the inner surfaces of the mould 14 and, on the other hand, by the peripheral edge 13 and by marginal regions 11a and 12a of the upper and lower faces of the pleated element 10.

A hardenable liquid composition 16 (see Fig. 3) for forming an encasement frame for the filter element 10 is now introduced into the mould cavity 15 under low pressure and allowed to solidify. The liquid composition may, for example, be a curable resin composition or maybe a molten thermoplastic that is allowed to solidify. As depicted by reference numeral 17, the liquid composition ingresses into the peripheral edge of the element 10.

Once the material has been solidified, the mould may be removed. The resulting product is a filter unit (see Fig. 3) comprising the filter element 10 provided with a peripheral encasing frame sealed to the element 10 (the seal being enhanced due to the aforementioned ingress of material).

It will be appreciated that the above described process allows relatively complex shaped H.E.P.A. filter elements to be encased and sealed effectively. This is useful for aesthetic and ergonomic design of, for example, high efficiency respirator filter masks.



Respirator filters are usually constructed using different layers, each with a specific function. These layers can include pre-filter scrims, pleated media packs, carbon blocks, electro static felts and heat/moisture exchange foam. All of these materials can be incorporated in the mould so that a composite unit is produced.

The illustrated process is also useful for vacuum cleaner design and allows air-flow systems and filters to be produced which are other than rectangular or circular.

CLAIMS

1. A method of forming a filter unit comprised of a filter element and an encircling peripheral encasement frame to which the filter element is sealed wherein the frame is moulded *in situ* by solidification of a liquid, solidifiable moulding composition provided around the periphery of the filter element.
2. A method as claimed in claim 1 wherein the frame is moulded so as partially to overlies a marginal region of at least one of the faces of the filter element.
3. A method as claimed in claim 1 or 2 comprising the steps of:
 - (i) providing a filter element having front and rear faces and a bonding peripheral edge,
 - (ii) locating around the peripheral edge of the element a mould unit which seals against peripheral regions of the front and rear faces and which together with the peripheral edge defines a mould cavity,
 - (iii) filling the mould cavity with a solidifiable, liquid moulding composition,
 - (iv) effecting conversion of the liquid to a solid, and
 - (v) removing the mould thereby producing the filter element.
4. A method as claimed in any one of claims 1 to 3 wherein the solidifiable, liquid moulding composition is a curable resin system.
5. A method as claimed in any one of claims 1 to 3 wherein the solidifiable, liquid moulding composition is a molten thermoplastic resin that solidifies on cooling.

6. A method as claimed in any one of claims 1 to 5 wherein the filter element is pleated.
7. A method as claimed in any one of claims 1 to 6 wherein the filter element is a H.E.P.A. filter element.
8. A method as claimed in any one of claims 1 to 6 wherein the filter element comprises U.L.P.A. (Ultra Low Penetration Air) media, ASHRAE media or a ePTFE laminate.
9. A method as claimed in any one of claims 1 to 5 wherein the filter element comprises a foam, pad or activated carbon.
10. A filter unit comprised of a filter element and a peripheral encasement frame sealed to the element wherein the frame has been moulded *in situ* around the filter element.
11. A filter unit as claimed in claim 7 wherein the filter unit is a H.E.P.A. filter unit.
12. A method for producing a filter unit substantially as hereinbefore described with reference to Figs. 2 and 3 of the accompanying drawings.
13. A filter unit substantially as hereinbefore described with reference to Fig. 3 of the accompanying drawings.





RECEIVED
 10-10-70
 10-10-70
 10-10-70




FIG 3

RECEIVED
 10-10-70
 10-10-70
 10-10-70

THE PATENT OFFICE

13 APR 2005

Received in Patents
International Unit